

FLEXALEN®600

Heating

Product code	Dimension	DN	Carrier pipe OD x s [mm]	Jacket pipe OD [mm]	Weight [kg/m]	min. bending Radius [m]	Coil ID [mm]	STD coil max. Length [m]	max. Diameter [m]	Coil Width max. [m]
STANDARD INSULATION RANGE										
Single line										
1010-090025-00	25 / 90	DN20	25 x 2.3	90	0,75	0,40	1500	300	2,4	1,2
1010-090032-00	32 / 90	DN25	32 x 3.0	90	0,86	0,40	1500	300	2,4	1,2
1010-090040-00	40 / 90	DN32	40 x 3.7	90	1,00	0,50	1500	300	2,4	1,2
1010-125050-00	50 / 125	DN40	50 x 4.6	125	2,08	0,70	1500	150	2,4	1,2
1010-125063-00	63 / 125	DN50	63 x 5.8	125	2,43	0,80	1500	150	2,4	1,2
Double line										
1030-125025-00	25 + 25 / 125	DN20	25 x 2.3	125	1,80	0,60	1500	150	2,4	1,2
1030-125032-00	32 + 32 / 125	DN25	32 x 3.0	125	1,90	0,60	1500	150	2,4	1,2
1030-160040-00	40 + 40 / 160	DN32	40 x 3.7	160	2,50	0,80	1500	100	2,4	1,2
1030-160050-00	50 + 50 / 160	DN40	50 x 4.6	160	3,00	0,80	1500	100	2,4	1,2
1030-200063-00	63 + 63 / 200	DN50	63 x 5.8	200	4,50	1,25	1500	50	2,4	1,2

Mega coil Length [m]	Mega coil Diameter [m]
----------------------------	------------------------------

500	2,9
500	2,9
500	2,9
300	2,9
300	2,9
300	2,9
300	2,9
150	2,9
150	2,9
100	2,9